

STAGEMAKER[®]

SR1 at a glance

Small but powerful

250 kg on one fall !

x2
**DOUBLE
BRAKE**
as standard
BGV D8+
READY

Technical characteristics

- > 1 fall (250 kg) or 2 falls hoist (500 kg).
- > Lifting speed : 4 m/min (1 fall).
- > Center to center hoist.
- > Clutch on the safe side.
- > Same iconic design that actual SR range (oval shape).
- > Hoist body : 100% aluminum body, no plastic parts.
- > Double brake as standard
- > Rotating upper and lower hooks.
- > DIN hooks.
- > Rubber ergonomic grip on top hook.
- > IP55 Protection.
- > 4x11 chain (same chain as SR2).
- > Available in Version A (direct control), Version B (Low voltage control).
- > Black CE P17 plug for better integration.
- > Black lifting chain.
- > Free maintenance brake.
- > RAL7021 epoxy paint.
- > Climbing hoist or industrial suspension configuration can be changed simply by reversing the chain container.
- > **PERFECT PUSH**. New patented concept, 5 pocket load wheel, fitted with 5 intermediate teeth. This innovation provides improved chain guiding and chair flow, to help reduce the risk of chain jamming.
- > **CHAINFLUX** as standard. Horizontal ejection of the chain.
- > Electric limit switch (on B version).

Stagemaker SR1	1 fall	2 falls
SWL (kg)	250	500
Dimensions	Best dimensions on the market with 1 or 2 brakes	Best dimensions on the market with 1 or 2 brakes
Body weight (kg)	10,4	10,4
Sound level	50 db	50 db
Integration into 12" truss	Yes	Yes
Double brake as standard	Yes	Yes
Chainflux as standard	Yes	Yes
PerfectPush as standard	Yes	Yes
Electric limit switch as standard	Yes (on low voltage type B version)	Yes (on low voltage type B version)
Versatile use of the hoist	Yes (Climbing hoist or industrial suspension just by reversing the hoist)	Yes (just by reversing the hoist)

Options

- > Version A or B.
- > Handles.

Stagemaker SR1 double brake fits perfectly in a 12" truss

